

## Calm Technical Data

|                           | Standard                           | Result                                                                               |
|---------------------------|------------------------------------|--------------------------------------------------------------------------------------|
| Tile size (mm)            |                                    | 228.6 x 1524 mm (09" x 60")                                                          |
| Toatal Thickness (mm)     |                                    | 5.0 mm                                                                               |
| Wear Layer Thickness (mm) |                                    | 0.55 mm                                                                              |
| Box Quantity              |                                    | 2.79 m <sup>2</sup> / 8 Planks / 23.20 kg                                            |
| Peeling Strength of Layer | EN431                              | Pass                                                                                 |
| Impact sound reduction    | ISO 717-2;2013                     | L <sub>nT,w</sub> 49                                                                 |
| Dimension stability       | EN434                              | 0.10%                                                                                |
| Colour fastness to light  | ISO 105 B02                        | ≥ Grade 6                                                                            |
| Static indentation        | EN433                              | ≤ 0.1 mm                                                                             |
| Embossing                 | Regular/Deep                       |                                                                                      |
| Flexibility               | EN435                              | Pass                                                                                 |
| Abrasion resistance       | EN660-2                            | Class T                                                                              |
| Castor chair resistance   | EN425                              | Pass                                                                                 |
| Slip resistance           | AS 4586-2013                       | P2                                                                                   |
| Fire rating               | AS. ISO 9239.1 2003                | Pass                                                                                 |
| Usage category            | EN685                              | 23/42                                                                                |
| Resistance to chemical    | EN423                              | Pass                                                                                 |
| Electrostatic properties  | EN1815                             | <2kv                                                                                 |
| Surface treatment         |                                    | PUR                                                                                  |
| UL Environmental          | UL 82386-4230                      | NSF/ANSI 332 - 2011 Silver - Sustainability Assessment for Resilient Floor Coverings |
| Environmental             | Floor score (SCS-ECI0.3-2014 v3.0) | Indoor Air Quality Certified; low VOC emissions                                      |
| Adhesive                  | ISO 9001 : 2008                    |                                                                                      |
| Quality Control Mgmt      |                                    |                                                                                      |
| Environmental Mgmt        | ISO 14001 : 2004                   |                                                                                      |



**For more information ☎ 07 3488 8115**

Email [info@decoline.com.au](mailto:info@decoline.com.au) Visit [www.decoline.com.au](http://www.decoline.com.au)